

Polar Controller™

The Polar Controller eliminates the need for CO2, dry ice, or separate fog machines. This refrigerated system can create an incredible 7000 cfm (198 cu. ft. per minute) of thick, white, dry, low-ground fog after a short 11 minute warm-up. Just add Chiller Tubes and fluid. Chiller Tubes are now included with the Polar Controller, resulting in a directional, lower, and colder fog.



Specifications

120vac #100101 (230vac, 50 Hz #100106)

Dims include fogger: 40" x 24" x 20"h (102cm x 61cm x 51cmh)

Weight: 197 lbs. (89kg.)

Voltage: 2x 120vac, 60 hz, 10a #100101 or
2x 230vac, 50 hz, 8a #100106

Type of Fog: Refrigerated thick, white, dry, low-ground fog made from Food Grade USP Propylene Glycol/Water base Fluid

Includes: 2 pcs 25' remote control with On/Off for each refrigeration/fog

DMX: Built in DMX, 2 channel, 5-pin XLR

Fluid: #150490 CITC's Low-Ground Fogging Fluid

Warm Up Time: 5-10 minutes

Continuous Fog: Up to 120 minutes at a time

Fog Heating Unit: 1500w continuous output w/new accelerator fan

Refrigeration Unit: 1200w

Circuit Breaker: 2-250vac, 15a

Limited warranty: one year with CITC fluids

Hoses: Includes connection adapter & 2 lengths of 5" x 8' chiller hose,



 www.facebook.com/CITCFX

(888) 786-CITC (425) 776-4950 info@citcfx.com www.citcfx.com Everett, WA USA