



MANIAC™ II

- 15 Second SmartFog creates cryogenic or fire effects
- Fully automated moving head
- 24 LED lights
- 10 DMX channels
- Adjustable output and speed
- Instant stop technology
- Strobe, dim, mix colors
- Mount upright or upside down
- Sound activation
- Multi-Function Controller allows use without DMX



1 YEAR WARRANTY

When using CITC

15 Second SmartFog Fluid #150495



Watch Demo Video!



/citcfx/



/citcfx/



/user/citcfx/

(425) 776-4950

info@citcfx.com

www.citcfx.com

SPECS

**120v #100122 w/ Controller #100124
(230v #100123 w/ Controller #100125)**

Dimensions: 19" x 18" x 22" (48.5 cm x 44 cm x 55.5 cm)

Weight: (Net / Gross) 39 lbs. (17.5 kg) / 56 lbs. (21.2 kg)

Fog Output: 20,000 ft³/min

Preheat Time: About 5 minutes

DMX Channels: 1-Fog volume, 2-red, 3-green, 4-blue, 5-amber, 6-color mixing, 7-strobe, 8-master dimmer, 9-pan, 10-tilt

LED Lamps: 5W RGBA x 24 (6 of each color)

Fluid Type: CITC SmartFog Fluid

Fluid Capacity: 1.31 qt. (1.2 L)

Sound Active: With optional Multi-Function Controller

Automatic Programs: With optional Multi-Function Controller

Demo Mode: With optional Multi-Function Controller

Pan 540°: Full rotation in approximately 2 sec.

Tilt 270°: Complete tilt range in about ¾ sec.

Electrical Supply: 1600W (100-120 VAC 15A 50/60 Hz) or (220-240 VAC 8A 50/60 Hz)

Electrical Breaker: 120VAC (15A – 250 VAC) 230VAC (8A – 250 VAC)

Multi-Function Controller

Dimensions: 4 3/8" x 3" x 1-11/16" (110 mm x 77 mm x 44.5 mm)

Weight: 1 lbs.

Sound Active: 6 Looping Sound Modes (4 with fog / 2 without fog)

Automatic Run Mode: 6 Looping Automatic Modes (4 with fog / 2 without fog)

Speed Adjustment: 10 Speed Settings

Sound Sensitivity: 10 Sound Sensitivity Settings

Fog Setting: 10 Timed Interval Settings

Compatibility: MANIAC™ & MANIAC II™

DMX Connector: 3-Pin Female XLR Output

Electrical Input: 100-240 VAC 50/60HZ

Electrical Output: 12VDC - 1A

