

MANIAC™ II

The Maniac II™ was designed for creative stage lighting designers wanting a unique, spectacular stage effect – it's fast, it's vibrant, and it's powerful! This machine is used best in Musical Performances, Nightclubs and Bars, Stadiums, Arenas.

FEATURES:

- 15 Second SmartFog creates cryogenic or fire effects
- Fully automated moving head
- 24 LED lights
- 10 DMX channels
- Adjustable output and speed
- Instant stop technology
- Strobe, dim, mix colors
- Mount upright or upside down
- Sound activation
- Multi-Function Controller allows use without DMX



1 YEAR WARRANTY

When using CITC 15 Second SmartFog Fluid #150495



MANIAC™ II SPECS

120v #100122 w/ Controller #100124

230v #100123 w/ Controller #100125

- **Dimensions:** 19" x 18" x 22" (48.5 cm x 44 cm x 55.5 cm)
- **Weight:** (Net / Gross) 39 lbs. (17.5 kg) / 56 lbs. (21.2 kg)
- **Fog Output:** 20,000 ft³/min
- **Preheat Time:** About 5 minutes
- **DMX Channels:** 1-Fog volume, 2-red, 3-green, 4-blue, 5-amber, 6-color mixing, 7-strobe, 8-master dimmer, 9-pan, 10-tilt
- **LED Lamps:** 5W RGBA x 24 (6 of each color)
- **Fluid Type:** CITC SmartFog Fluid
- **Fluid Capacity:** 1.31 qt. (1.2 L)
- **Sound Active:** With optional Multi-Function Controller
- **Automatic Programs:** With optional Multi-Function Controller
- **Demo Mode:** With optional Multi-Function Controller
- **Pan 540°:** Full rotation in approximately 2 sec.
- **Tilt 270°:** Complete tilt range in about ¾ sec.
- **Electrical Supply:** 1600W (100-120 VAC 15A 50/60 Hz) or (220-240 VAC 8A 50/60 Hz)
- **Electrical Breaker:** 120VAC (15A – 250 VAC) 230VAC (8A – 250 VAC)

Multi-Function Controller

- **Dimensions:** 4 3/8" x 3" x 1-11/16" (110 mm x 77 mm x 44.5 mm) Weight: 1 lbs.
- **Sound Active:** 6 Looping Sound Modes (4 with fog / 2 without fog)
- **Automatic Run Mode:** 6 Looping Automatic Modes (4 with fog / 2 without fog)
- **Speed Adjustment:** 10 Speed Settings
- **Sound Sensitivity:** 10 Sound Sensitivity Settings
- **Fog Setting:** 10 Timed Interval Settings
- **Compatibility:** MANIAC™ & MANIAC II™
- **DMX Connector:** 3-Pin Female XLR Output
- **Electrical Input:** 100-240 VAC 50/60HZ
- **Electrical Output:** 12VDC - 1A